

Specification Sheet for Lite Storm 2

Axle Length	36.75" on Twin Cams	36" on Omega Cam
Brace Height	6.5" – 7"	
Limb Length	16"	

*Note:- Brace heights may vary depending on cam size and type. It is more important to use the axle length as a point of reference, more than the brace height.

STRING AND CABLE CHARTS

	String	Power Cable	Control Cable	Split Cable (Long)	Split Cable (Short)
<i>Omega No.1</i>	58.5	37.75	39.75	-	-
<i>Omega No.2</i>	54.5	37.75	39.75	-	-
<i>Omega No.3</i>	51.5	37.75	39.75	-	-
<i>Rapid 2 No.R2</i>	54.75	38.25	-	58.5	9.5
<i>Rapid 2 No.R3</i>	51.75	38.25	-	58.5	9.5
<i>Rapid 2 No.R4</i>	48.25	38.25	-	58.5	9.5

MODULE SELECTION CHARTS

OMEGA CAM	OM1	OM2	OM3	OM4	OM5
<i>Cam No.1</i>	30.5	30	29.5	29	28.5
<i>Cam No.2</i>	28	27.5	27	26.5	26
	XM1	XM2	XM3	XM4	XM5
<i>Cam No.3</i>	25.5	25	24.5	24	23.5

RAPID 2 (Target Module)	RP1	RP2	RP3	RP4	RP5
<i>Cam No.R2</i>	29	28.5	28	27.5	27
<i>Cam No.R3</i>	27	26.5	26	25.5	25
<i>Cam No.R4</i>	25	24.5	24	23.5	23

RAPID 2 (Turbo Module)	TB1	TB2	TB3	TB4	TB5
<i>Cam No.R2</i>	29	28.5	28	27.5	27
<i>Cam No.R3</i>	27	26.5	26	25.5	25
<i>Cam No.R4</i>	25	24.5	24	23.5	23