

Specification Sheet for Supernova (41.5" 40.25")

Axle Length	41.5"	40.25" Omega Cam
Brace Height	8"	9" Omega Cam
Limb Length	16"	

*Note:- Brace heights may vary depending on cam size and type. It is more important to use the axle length as a point of reference, more than the brace height.

STRING AND CABLE CHARTS

	String	Power Cable	Control Cable	Split Cable (Long)	Split Cable (Short)
<i>Omega No.1</i>	62.5	41.75	43.75	-	-
<i>Omega No.2</i>	58.5	41.75	43.75	-	-
<i>Omega No.3</i>	55.5	41.75	43.75	-	-
<i>Rapid 2 No.R2</i>	59.5	43	-	68	9.5
<i>Rapid 2 No.R3</i>	56.5	43	-	68	9.5
<i>Rapid 2 No.R4</i>	53	43	-	68	9.5
<i>T-Wheel No.1</i>	60 (61 for 30-31)	43	-	68	9.5
<i>T-Wheel No.2</i>	57	43	-	68	9.5
<i>T-Wheel No.3</i>	55	43	-	68	9.5
<i>T-Wheel No.4</i>	51.5	43.5	-	68	10

MODULE SELECTION CHARTS

OMEGA CAM	OM1	OM2	OM3	OM4	OM5
<i>Cam No.1</i>	33.5	33	32.5	32.	31.5
<i>Cam No.2</i>	31	30.5	30	29.5	29
	XM1	XM2	XM3	XM4	XM5
<i>Cam No.3</i>	28.5	28	27.5	27	26.5

RAPID 2 (Target Module)	RP1	RP2	RP3	RP4	RP5
<i>Cam No.R2</i>	32	31.5	31	30.5	30
<i>Cam No.R3</i>	30	29.5	29	28.5	28
<i>Cam No.R4</i>	28	27.5	27	26.5	26

RAPID 2 (Turbo Module)	TB1	TB2	TB3	TB4	TB5
<i>Cam No.R2</i>	32	31.5	31	30.5	30
<i>Cam No.R3</i>	30	29.5	29	28.5	28
<i>Cam No.R4</i>	28	27.5	27	26.5	26

T-WHEEL	HS1 65% SS1 65%	HS1 55% SS1 55%	HS2 65% SS2 65%	HS2 55% SS2 55%
<i>Cam No.1</i>	30		29	
<i>Cam No.2</i>	28		27	
<i>Cam No.3</i>	27		26	
<i>Cam No.4</i>	25		24	