

Specification Sheet for Supernova (43")

Axle Length	43"
Brace Height	8.5"
Limb Length	17"

*Note:- Brace heights may vary depending on cam size and type. It is more important to use the axle length as a point of reference, more than the brace height.

STRING AND CABLE CHARTS

	String	Power Cable	Control Cable	Split Cable (Long)	Split Cable (Short)
<i>Omega No.1</i>	65	44	46	-	-
<i>Omega No.2</i>	61	44	46	-	-
<i>Omega No.3</i>	58	44	46	-	-
<i>Rapid 2 No.R2</i>	61	44	-	70.25	9.5
<i>Rapid 2 No.R3</i>	58	44	-	70.25	9.5
<i>Rapid 2 No.R4</i>	54.5	44	-	70.25	9.5
<i>T-Wheel No.1</i>	62	44	-	70.25	9.5
<i>T-Wheel No.2</i>	58	44	-	70.25	9.5
<i>T-Wheel No.3</i>	56	44	-	70.25	9.5
<i>T-Wheel No.4</i>	52.5	44.5	-	70.25	10

MODULE SELECTION CHARTS

OMEGA CAM	OM1	OM2	OM3	OM4	OM5
<i>Cam No.1</i>	34	33.5	33	32.5	32
<i>Cam No.2</i>	31.5	31	30.5	30	29.5
	XM1	XM2	XM3	XM4	XM5
<i>Cam No.3</i>	29	28.5	28	27.5	27

RAPID 2 (Target Module)	RP1	RP2	RP3	RP4	RP5
<i>Cam No.R2</i>	33	32.5	32	31.5	31
<i>Cam No.R3</i>	31	30.5	30	29.5	29
<i>Cam No.R4</i>	29	28.5	28	27.5	27

RAPID 2 (Turbo Module)	TB1	TB2	TB3	TB4	TB5
<i>Cam No.R2</i>	33	32.5	32	31.5	31
<i>Cam No.R3</i>	31	30.5	30	29.5	29
<i>Cam No.R4</i>	29	28.5	28	27.5	27

T-WHEEL	HS1 65% SS1 65%	HS1 55% SS1 55%	HS2 65% SS2 65%	HS2 55% SS2 55%
<i>Cam No.1</i>	31		30	
<i>Cam No.2</i>	29		28	
<i>Cam No.3</i>	28		27	
<i>Cam No.4</i>	26		25	